

Multi Language Customer Display



EC-VFD-3015

Features

- Vacuum Fluorescent Display
- Supports 32 sets of international Characters
- Innovative hinge design enables easy angle adjustment
- Display adjustable range : 0-355° horizontally, 0-90° vertically



Specifications

Display Type	Vacuum fluorescent Display
Number of Characters	40 (20 columns x 2 lines)
Brightness	500~1000 cd/m ²
Character Font	5 x 7 Dot Matrix
Character Type	95 Alphanumeric, 32 International Characters
Character Size	9.02(H) x 5.25(W) mm
Dot Size	0.86 x 1.05 mm
Download Characters	9 characters
Interface	RS-232(Serial)/ USB
Command Set	LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL, ICD2002, EZ-202, PL-200, PD3000
Power Supply	DC 5~24V
Power Consumption	1.5W
MTBF	30,000 hrs
Panel Dimemsion (W x D x H)	200 W x 77.5 D x 31 H (mm)
Support Dimemsion (H x Ø)	140 H x 34.5 Ø (mm)
Base Dimemsion (W x D x H)	169.5 W x 98.5 D x 39 H (mm)
Weight	0.98KGs
Viewing Angle	Max 60
Horizontal Rotation	Max. 355

Asia, Pacific & Europe: Unit A, 2/F, Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx