

1D Handheld

Barcode Scanner



- Self knowledge property right, personalized customization is welcome
- Support serial port command setting, make the second development convenient
- Firmware update online with USB cable.
- Support black and white inverse barcode decode.
- Aggressive scanning performance on difficult codes. (low print contrast, damaged, fuzzy and long codes)



XL-6500



Light Source	Visible Laser Diode 650nm
Scan Pattern	Single Scan
Decode Rate	300 times/second
Scan Precision	4mil
Scan Width	30mm@scan window, 220mm@200mm
Scan Depth of field	0-330mm (0.33mm pcs0.9)
Elevation Angle	65
Deflection Angle	55
Support Interface	PS-2(KB); RS-232; USB-HID; USB-Virtual COM
Print Contrast	20% UPC/EAN 100%
Mention Pattern	Buzzer, Indicator

Size	L x W x H: 175mm x 73mm x 102mm
Weight	246g
Material	ABS+PC
Voltage	5VDC
Operating Current	85mA
Static Current	30mA
EMC	CE & FCC DOC compliance
Operating Temperature	- 0°C to 50°C
Storage Temperature	- 40°C to 70°C
Humidity	5% to 85% relative humidity, non-condensing
Light Levels	Daylight, 3000-8000LUX



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F, No.7, Kehui First Street, Science Road, Science City, Guangzhou, China
 Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com