

EC Thermal Receipt Printer



EC-PM-C250

Features

- Fast 250 mm/s printing speed
- ESC/POS & LINE/T command sets compatible
- 203 dpi high quality receipt printout
- Multi-interface (Serial+USB+Ethernet)
- Windows driver, Linux driver available

Specifications

Print method	Direct thermal line
Resolution	203dpi
Print width	64/72 mm
Print speed	250mm/s
Paper Diameter	80mm
Interface	Serial+USB+Ethernet
Character Size	ANK Font Font A: 12×24dots Font B: 9×17dots Simplified/Traditional Chinese Character: 24×24dots
Driver	Windows 9X / WIN ME / WIN 2000 / WIN NT / WIN XP / WIN 7 / WIN 8 / WIN 10 / Linux
Fonts	GB2312
Data Buffer	8K bytes
NV Flash	60K bytes
Power Cashdrawer out	DC 24V/2.5A
Power Supply	AC 110V/240V, 50 ~ 60Hz, DC 24V/2.5A
Work environment	Temperature: 0 ~ 45°C, Humidity:10 ~ 80%
Storage environment	Temperature: -10 ~ 60°C, Humidity:10 ~ 90%
Reliability- Mechanism	>150km
Reliability-Auto Cutter	1.5 Million Cuts
MTBF	360,000 Hours
Weight	1 kg
Dimension	128(W) × 166(L) × 126(H) mm



Asia, Pacific & Europe: Unit A, 2/F, Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx